

e-STUDIO™ 2010AC

e-STUDIO™ 2510AC

- > Colour Multifunction Printer
- > Up to 25 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



e-STUDIO™ 2010Ac/2510Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	10.1" Colour WSVGA Touch Screen Tilting Display
Copy Speed	20/25 PPM (A4)
First Copy Out	Colour: 9.5/9.5 seconds Monochrome: 7.1/7.1 seconds
Warm-Up Time	Approx. 21 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	100 x 148 mm to A3, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 350 Sheets/Max. 2,900 Sheets
Original Feed	Optional 100-Sheet RADF
Scan Speed & Weights	RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 35-157 gsm, Duplex: 50-157 gsm
Max. Original Size	A3
Paper Feed Sizes	Drawer 1: 250 Sheets-A5-R to A3 Stack Feed Bypass: 100 Sheets- 100 x 148 mm to A3 Opt. Paper Feed Unit: 550 Sheets-A5-R to A3 Opt. 550-Sheet Paper Feed Pedestal-A5-R to A3 Opt. 550-Sheet Drawer for PFP-A5-R to A3 Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-16K-R to A4-R Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-A4 Only
Paper Weights	Standard: 250 Sheets- 60-163 gsm Stack Feed Bypass: 100 Sheets-60 -209 gsm Opt. Paper Feed Unit: 550 Sheets- 60-163 gsm Opt. 550-Sheet Paper Feed Pedestal: 60-163 gsm Opt. 550-Sheet Drawer for PFP: 60-163 gsm Opt. Envelope Cassette for PFP: 60- 163 gsm Opt. 2,000-Sheet Tandem LCF (Pedestal Type): 64-105 gsm Standard Automatic Duplex Unit: 60-163 gsm
Duplex	25% to 400%
Reproduction Ratio	Max. 67.2K Month (e-STUDIO 2010Ac) Max. 84K Month (e-STUDIO 2510Ac)
Max Duty Cycle	Approx. 57 kg
Weight	575 mm (W) x 586 mm (D) x 787 mm (H)
Approx. Dimensions	CMY: 33.6K, BK: 38.4K @ 5%
CMYK Toner Yield	220-240 Volts, 50/60 Hz, 12 Amps
Power Source	Maximum 2.0kW (220-240V)
Power Consumption	Intel Atom™ 1.33GHz (Dual-Core)
CPU	2GB, Max. 4GB
Memory	320GB Self-Encrypting Drive
Hard Disk Drive	

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	20/25 Pages Per Minute (A4)
Print Resolution	600 x 600 dpi (5 bit), 600 x 1,200 dpi (1 bit) PS3 Only
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (bi-directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess, EFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)*, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, NFC Authentication

*Conformance with HCD-PPv1.0 in High security mode.

ENERGY STAR® (V2.0), Blue Angel Mark (RAL UZ-205, MFD)

WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Stds. Certification

Scan Specifications

Scan Speed	RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Colour/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options		
RADF	MR-3031-B	IPsec Enabler GP-1080
Platen Cover	KA-5005PC	Unicode Font Enabler GS-1007
Additional Paper Options		
Paper Feed Pedestal	KD-1058-B	Embedded OCR Enabler Single License GS-1080
Paper Feed Unit	MY-1047-B	Five Licenses GS-1085
Drawer Module	MY-1048-B	Multi-Station Print Enabler Single License GS-1090
Envelope Cassette Option	MY-1049-B	Five Licenses GS-1095
Large Capacity Feeder	KD-1059A4-B	USB Hub Option GR-1310
Finishing Options		
Inner Finisher	MJ-1042-B	SharePoint® Connector GB-1440
Saddle-Stitch Finisher	MJ-1110-B	Exchange Connector GB-1450
Hole Punch Unit (For MJ1042)	MJ-6011	Google Docs™ Connector GB-1540
Hole Punch Unit (For MJ1110)	MJ-6105	External Interface Enabler -
Bridge Kit	KN-5005	Data OverWrite Enabler GP-1070
Job Separator	MJ-5014	Monotype Font Option GB-2050
Connectivity/Security Options		
FAX Unit/2nd Line for FAX Unit	GR-1370EU	Miscellaneous Options
Wireless LAN/Bluetooth	GN-4020	Stand
Accessory Tray	GR-1330	Accessible Arm KK-2560
Panel 10-Key Option	GR-1340	Work Tray KK-5005
Card Reader Holder	GR-1320	Manual Pocket KK-5008
4GB Memory Option	GC-1410	Harness Kit for Coin Controller GQ-1280
FIPS HDD	GE-1230	
Hardcopy Security Printing	GP-1190A	
Meta Scan Enabler	GS-1010	



FMA Group Co., Ltd. (Near BTS Saladeang Station)
10/15 Convent Rd., Silom, Bangkok 10500
Tel: 02-235-0156, 02-238-1350 Fax: 02-236-6594, 02-235-8856
sales@fma.co.th www.fma.co.th

Hotline: 02-631-1130
 FMA Group Co., Ltd.
More than 40 Years of Experience