

TOSHIBA

Intelligent MFP that meets today's challenging business requirements

- > Colour Multifunction Printer
- > Up to 40 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready

e-STUDIO330AC

e-STUDIO400AC



**TOGETHER
INFORMATION**

TOSHIBA

e-STUDIO330Ac/400Ac



Main Specifications

Copy System	Indirect electrostatic photographic method
Display	10.1" LCD touch-screen resistive type
Copy Speed	33 / 40 cpm (A4) 27 / 33 cpm (B4)
First Copy Out	330AC: 5.7 seconds (mono) / 7.2 seconds (colour) (300 dpi scan) 400AC: 5.1 seconds (mono) / 6.3 seconds (colour) (300 dpi scan)
Warm-Up Time	After Powering On: Approx. 20 seconds From Sleep Mode: 18 seconds (e-S330AC) / 18 seconds (e-S400AC) From Low-power Mode: 18 seconds (e-S330AC) / 18 seconds (e-S400AC)
Stack Feed Bypass	A4 / 52 - 256 gsm / Banner (215.9 x 1320.8 mm) / 90 - 163 gsm
Multiple Copying	Up to 999 copies
Paper Capacity	Standard Drawer x 1: 550 sheets x 1 Standard Stack Feed Bypass: 100 sheets Optional Paper Feed Unit (PFU): 550 sheets Optional LCF (Pedestal Type): 2,000 sheets
Original Feed	100 - Sheet DSDP
Feeding Speed	58 (A4)
Max. Original Size	A4 / Legal
Paper Feed Sizes	Drawer 1: 550 Sheets A4 to A5 Stack Feed Bypass: 100 Sheets - A4 - 98 mm x 148 mm, Legal, Banner Standard: 550 Sheets - 60 - 256 gsm Stack Feed Bypass: 100 Sheets - 52 - 256 gsm
Paper Weights	A4 - A5 / 60 - 256 gsm
Duplex	25% to 400%
Reproduction Ratio	Approx. 53 kg
Weight	520 mm (W) x 540 mm (D) x 634 mm (H)
Approx. Dimensions	220 - 240 Volts, 50 / 60 Hz, 12 Amps
Power Source	Max. 2.0kW (220 - 240V)
Power Consumption	Super sleep: 0.7W
CPU	Intel Apollo Lake E3930 (Dual Core)
Memory	4 GB (Main memory + Page memory)
Hard Disk Drive	320 GB Toshiba Secure HDD

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	33 / 33 / 40 / 40 cpm (A4 size) (Mono/ Colour)
Print Resolution	600 dpi x 600 dpi, 3bit (All PDL) 1,200 dpi x 1,200 dpi, 1bit (PS Driver)
Operating Systems	Windows® 8.1, 10, Windows Server® 2012 / R2, Windows Server® 2016, Windows Server® 2019, Macintosh® (MacOS X 10.6.8, 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional IEEE802.11b/g/n, Optional Bluetooth
Mobile Service	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess, e-Suite
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Security Features	User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication *Conformance with HCD-PPv1.0 in High security mode.
Certification	WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Scan Specifications

Scan Speed	Monochrome: 58/116 SPM Colour: 40/80 SPM (300 dpi), 20/40 SPM (400 dpi, 600 dpi)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi / Single Page, PDF-Multi / Single Page, Searchable PDF (Opt.), XPS-Multi / Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour / Grayscale: JPEG, TIFF-Multi / Single Page, PDF-Multi / Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi / Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Colour / Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3, G3
Data Compression	JBIG, MMR, MR, MH
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	33.6kbps ~2.4kbps (automatic fall-back)
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

Accessories (Options)

Paper Handling Options	
Paper Feed Unit (550 sheets)	MY-1050
Large Capacity Feeder (2,000 sheets)	KD-1071
Spacer	GR-1380
Caster	GR-1390
Offline Stapler	MJ-1047
Staple Cartridge for offline stapler	Stapler-3700
Desk	MH-330AC
System Options / Accessories	
FAX Unit / 2nd line for FAX Unit	GD-1370EU
Wireless LAN / Bluetooth Module	GN-4030
Harness kit for coin controller	GQ-1280-N
Card Reader Holder	GR-1400
Panel Ten Key Option	GR-1340
FIPS HDD Option	GE-1230
License Enabler Options	
Data Overwrite enabler (license)	GP-1070Node
Meta scan enabler	GS-1010Node
IPSec enabler	GP-1080Node
Unicode Font enabler	GS-1007Node
Embedded OCR enabler (license)	GS-1080Node
Multi Station Print (license)	GP-1090Node
IP Fax License	GS-1100Node
Hardcopy Security Kit	GP-1190Node
e-BRIDGE Plus for Zone OCR V3.0 (Node)	GB-2330Node
e-BRIDGE Plus for OneDrive for Business V3.0 (Node)	GB-2300Node
e-BRIDGE Plus for SharePoint Online V3.0 (Node)	GB-2310Node
e-BRIDGE Plus for Exchange Online V3.0 (Node)	GB-2320Node
e-BRIDGE Plus for Gmail (Node)	GB-2380Node
e-BRIDGE Plus for G Suite Google Drive (Node)	GB-2390Node
Other Options	
Accessible Arm	KK-2560



FMA Group Co., Ltd. (Near BTS Saladeang Station)

10/15 Convent Rd., Silom, Bangkok 10500

Tel: 02-235-0156, 02-238-1350

Fax: 02-236-6594, 02-235-8856

sales@fma.co.th www.fma.co.th

Hotline: 02-631-1130

More than 40 Years of Experience



Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Productivity and paper specifications are related to paper size of A4 and a paper weight of 80 g/m2 if not otherwise mentioned.

Copyright ©2020 TOSHIBA TEC.