

e-STUDIO™ 2515AC

e-STUDIO™ 3015AC

e-STUDIO™ 3515AC

e-STUDIO™ 4515AC

e-STUDIO™ 5015AC

- > Colour Multifunction Printer
- > Up to 50 PPM
- > Medium/Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Solutions Ready



e-STUDIO™ 2515Ac/3015Ac/3515Ac/4515Ac/5015Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	10.1" Colour WSVGA Touch Screen Tilting Display
Copy Speed	25/30/35/45/50 PPM (A4)
First Copy Out	Colour: 7.8/7.8/7.8/5.7/5.7 seconds Monochrome: 5.9/5.9/5.9/4.4/4.4 seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	100 x 148 mm to 320 x 460 mm, 305 x 1200 mm Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSDf or 100-Sheet RADF
Scan Speed & Weights	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour), Simplex: 35 - 209 gsm, Duplex: 35 - 209 gsm RADF Scan: Up to 73 IPM (Monochrome or Colour), Simplex: 35 - 157 gsm, Duplex: 50 - 157 gsm
Max. Original Size	A3
Paper Feed Sizes	Drawer 1: 550 Sheets-A5-R to A3 Drawer 2: 550 Sheets- A5-R to 320 x 460 mm Stack Feed Bypass: 100 Sheets- 100 x 148 mm to 320 x 460 mm, 305 x 1,200 mm Banner Opt. 550-Sheet Paper Feed Pedestal- A5-R to 320 x 460 mm Opt. 550-Sheet Drawer for PFP- A5-R to 320 x 460 mm Opt. Envelope Cassette for PFP- Approx. 60 Envelopes/550 Sheets-16K-R to A4-R Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-A4 Only Standard: 550 Sheets x 2- 60 - 256 gsm Stack Feed Bypass: 100 Sheets- 52 - 280 gsm Opt. 550-Sheet Paper Feed Pedestal- 60 - 256 gsm Opt. 550 Sheets Drawer for PFP- 60 - 256 gsm Opt. Envelope Cassette for PFP- 60 - 256 gsm Opt. 2,000-Sheet Tandem LCF (Pedestal Type)- 64 - 105 gsm Standard Automatic Duplex Unit (60 - 256 gsm)
Paper Weights	25% to 400% Max. 75K/90K/105K/105K/105K Month (Colour: 100%) Max. 150K/180K/210K/210K/210K Month (Monochrome: 100%) Approx. 78.1 kg 585mm (W) x 641mm (D) x 787 mm (H) CMY: 33.6K, K: 38.4K @ 5% 220-240 Volts, 50/60 Hz, 12 Amps Maximum 2.0kW (220-240V) Intel Atom™ 1.33 GHz (Dual-Core) 4GB 320GB Self-Encrypting Drive
Duplex	
Reproduction Ratio	
Max Duty Cycle	
Weight	
Approx. Dimensions	
CMYK Toner Yield	
Power Source	
Power Consumption	
CPU	
Memory	
Hard Disk Drive	

Security Features

Timeout and Audible Beep Message Alerts
User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for firmware update, Integrity Check function, Image Log, Card Authentication, NFC Authentication
*Conformance with HCD-PPv1.0 in High security mode.
ENERGY STAR® (v2.0), Blue Angel Mark (RALUZ-205, MFD), Nordic Swan, RoHS WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Stds. Certification

Scan Specifications

Scan Speed	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Colour) RADF Scan: Up to 73 IPM (Monochrome or Colour)
Scan Modes	Standard: Full Colour, Auto Colour, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Colour/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Colour/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Colour Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
DSDf	MR-4000-B	Meta Scan Enabler	GS-1010
RADF	MR-3031-B	IPsec Enabler	GP-1080
Platen Cover	KA-5005PC	Unicode Font Enabler	GS-1007
		Embedded OCR Enabler	
Additional Paper Options		Single License	GS-1080
Paper Feed Pedestal	KD-1058-B	Five Licenses	GS-1085
Drawer Module	MY-1048-B	Multi-Station Print Enabler	
Envelope Cassette Option	MY-1049-B	Single License	GS-1090
Large Capacity Feeder	KD-1059A4-B	Five Licenses	GS-1095
		SharePoint® Connector	GB-1440
Finishing Options		Exchange Connector	GB-1450
Inner Finisher	MJ-1042-B	Google Docs™ Connector	GB-1540
50-Sheet Staple Finisher	MJ-1109-B	Data OverWrite Enabler	GP-1070
Saddle-Stitch Finisher	MJ-1110-B	Hardcopy Security Printing	GP-1190A
Hole Punch Unit for MJ1042	MJ-6011	FIPS HDD	GE-1230
Hole Punch Unit for MJ1109/MJ1110	MJ-6105	Monotype Font Option	GB-2050
Bridge Kit	KN-5005		
Job Separator	MJ-5015	Miscellaneous Options	
		Stand	
Connectivity/Security Options		Accessible Arm	KK-2560
FAX Unit/2nd Line for FAX Unit	GD-1370	Work Tray	KK-5005
Wireless LAN/Bluetooth	GN-4020	Manual Pocket	KK-5008
Hardcopy Security Printing	GP-1190A	Harness Kit for Coin Controller	GQ-1280
Bluetooth Keyboard	GR-9000		
Accessory Tray	GR-1330		
Panel 10-Key Option	GR-1340		
Card Reader Holder	GR-1320		
USB Hub	GR-1310		

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	25/30/35/45/50 Pages Per Minute (A4)
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Colour/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 only) (BW/with Smoothing) PS3 Only)
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7.8.1,10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk™, Port 9100 (bi-directional), NetWare P-SERVER LPD w/iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), MacOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-speed) Optional IEEE802.11b/g/n, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess, EFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen



FMA Group Co., Ltd. (Near BTS Saladeang Station)

10/15 Convent Rd., Silom, Bangkok 10500

Tel: 02-235-0156, 02-238-1350 Fax: 02-236-6594, 02-235-8856

sales@fma.co.th www.fma.co.th



Hotline: 02-631-1130

FMA Group Co., Ltd.

More than 40 Years of Experience